

Technical data sheet LM740

Specification Club chair, four-star base

Dimensions in mm	Backrest:	H:	340	
		Seat:	H: 440 W: 465 D: 460	
	Total:	H:	810	
		W (ArmR):	610	
	Packaging data	Weight:	kg	12,3
		Volume:	m³	0,4



Basic equipment

Benefit

Seat shell	Seat shell can be rotated all the way round, upholstered.	Very comfortable to sit on, with a harmonious appearance too.
Backrest	Backrest height 350 mm, padded, fully upholstered.	Can be placed anywhere in the room, with integrated armrest.
Upholstery	Upholstered seat, 40 mm foam, free of CFCs and chlorinated hydrocarbons (foam of one type).	Extremely comfortable to sit on.
Base	Four-star aluminium, powder-coated black.	Attractive look.
Glides	Hard conference glides for soft floors. Black base = black glides.	Firm contact with the floor.
Cover materials	Various fabric and leather qualities in various colours.	There are numerous colours and cover materials to choose from when designing.
Materials used	All materials can be separated and recycled.	Environmentally friendly.
Certification	Quality management system DIN EN ISO 9001:2008, VO (EC) no. 1221/2009 (EMAS), environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis Gold, Blue Angel.	High-quality product.
Standards	DIN EN 16139 Non-domestic seating. Tested for harmful substances. GS mark for tested safety	Extremely safe.
Guarantee and returns	10 years long-term. Full return and recycling guarantee.	Free-of-charge replacement of parts within the guarantee period.

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet LM740

Specification Club chair, four-star base

Dimensions in mm	Backrest:	H:	340
		Seat:	H: 440 W: 465 D: 460
	Total:	H:	810
		W (ArmR):	610
		D:	570
	Packaging data	Weight:	kg
Volume:		m³	0,4



Options	Benefit
<p>Base</p> <p>Four-star aluminium, powder-coated brilliant silver, polished. Veener: oak, walnut.</p>	<p>Attractive look.</p>
<p>Glides/castors</p> <p>Soft conference glides for hard floors. Soft castors, load-dependent braked, for hard floorings (in accordance with DIN EN 12529). Hard double castors, load-dependent braked, for soft floorings. (In accordance with DIN EN 12529). Polished base = chrome-look castors/glides.</p>	<p>Firm contact with the floor. The chair does not roll away when it is unoccupied, which minimises the risk of accidents.</p>

Disassembly instructions are available upon request for any interstuhl product